

---

# SMPTE STABLE DOCUMENT

---



**The attached SMPTE Engineering Document has been declared “Stable” by the controlling Technology Committee.**

**The SMPTE Operations Manual for Standards states:**

*A document should be stabilized if it is believed to be substantially correct, does not contain harmful or misleading recommendations, may still be relevant to equipment or practices in use, is stable, but does not represent current technology, and need not be subject to future reviews.*

*A Stable document shall still be made available and offered for sale by the Society, but it shall be prefaced by a cover page explaining its current status.*

*At any time, a Technology Committee may revise, amend, or otherwise initiate a new Project on a Stable document.*

**A Stable document is “In Force”, and not deprecated or withdrawn.**

**\* \* \* \* \***

**Note:**

**SMPTE “Stable” documents were previously described as “Archived” and the attached document may be marked as “Archived”. The status of a SMPTE document described as “Archived” is exactly as described above for a “Stable” document.**

**Stable documents may not adhere to the latest style and format of SMPTE documents, or to current usage of normative language. Suitable care should be taken in interpretation.**

# SMPTE RECOMMENDED PRACTICE

**RP 63-2002**

Revision of RP 63-1997

## Specifications for Sound-Focusing Test Film for 16-mm Audio Reproducers, Photographic Type



Page 1 of 2 pages

### 1 Scope

This practice specifies a test film for use in focusing the scanning beam of 16-mm motion-picture photographic audio reproducers operating at 36 ft (11 m) per minute.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this practice. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this practice are encouraged to investigate the possibility of applying the most recent edition of the standards indicated below.

AES 6-1982, Method for Measurement of Weighted Peak Flutter of Sound Recording and Reproducing Equipment

ANSI/SMPTE 109-1998, Motion-Picture Film (16-mm) — Perforated 1R and 2R

SMPTE 41-1999, Motion-Picture Film (16-mm) — Prints — Photographic Audio Records

SMPTE 223M-2001, Motion-Picture Film — Safety Film

### 3 Test film signal

#### 3.1 Frequency

The audio record on the film shall reproduce at a frequency of 7000 Hz  $\pm$  100 Hz (type A) or 5000 Hz  $\pm$  100 Hz (type B) when the linear speed of the film is 24 perforations per second or approximately 36 ft per minute (7.2 in or 18.3 cm per second).

##### 3.1.1 Type A

A film with a 7000-Hz record to be used by manufacturers and laboratories, for precise adjustment of the sound-focusing system.

##### 3.1.2 Type B

A film with a 5000-Hz record to be used when simpler instruments are available or when lower quality is adequate, for quick adjustment of the sound-focusing system.

### **3.2 Audio record**

The location and dimensions of the recorded audio record shall be in accordance with SMPTE 41.

### **3.3 Recording**

The film shall have an originally recorded, variable-density audio track. The track shall be heavily overmodulated and developed to high contrast so that it is essentially a square-wave track. The signal level shall not fluctuate more than  $\pm 0.5$  dB within the test film length.

### **3.4 Flutter**

The weighted peak flutter of the audio record shall not exceed 0.1% when measured in accordance with AES 6.

### **3.5 Azimuth**

The azimuth of the audio record shall be  $90^\circ \pm 3'$  to the reference edge of the film.

## **4 Film stock**

**4.1** The film stock, preferably polyester, shall be splice-free, of the low-shrinkage, safety type in compliance with SMPTE 223M, and cut and perforated in accordance with long-pitch dimensions specified in ANSI/SMPTE 109.

**4.2** In the event that triacetate film stock is used, it shall be splice-free and shall have a maximum lengthwise shrinkage of 0.50% when tested as follows: At least 20 strips of film approximately 31 inches in length shall be cut for measurement of shrinkage. After normal development and drying (not over 80°F [27°C]), the strips shall be placed at least 1/4 in apart in racks and kept for seven days in an oven maintained at 120°F (49°C) and a relative humidity of 20%. The strips shall then be removed, reconditioned thoroughly to 50% relative humidity at 70°F (21°C), and the shrinkage measured by a suitable method. The percent shrinkage shall then be calculated on the basis of deviation from the nominal dimension for the length of 100 consecutive perforation intervals given in ANSI/SMPTE 109.

## **5 Identification**

Each test film shall be identified by a suitable identification marking. This marking shall be printed lengthwise in the picture area and the spacing between consecutive titles shall be approximately 12 in (30 cm).